

							
Home	About Vector	Distributors	Sales	Contact Us	Catalog Request		

## VMEE-M EXTENDER VECTORBORD®



6U VME J1/J2 with 3-row, 96 positions DIN 41612 style connectors ( click on image to enlarge)

### KEY FEATURES :

- [VMEEJ1](#) Extender on top & [VMEEJ2](#) Extender on Bottom, new monolithic design [VMEE-M](#) Extender
- Excellent performance with a multi layer design
- Individual signal tracking with interruption option
- Voltage & Current measuring facilities
- Full ground plane
- Signal pin-out identification silkscreen onto outer PCB layers
- Jumper Blocks provided to allow signal line interrogation
- Max. current per contact @ nominal 50° C = 1.75A
- Controlled impedance, Signal trace shielding
- Voltage rating 200 RMS or 300 VDC
- [DOWNLOAD DATASHEET](#)

### BOARD SPECIFICATIONS :

- Material : FR-4 Epoxy Glass
- PCB UL94V-0, PCB RoHS Compliant
- 6 Internal 1oz. copper layers
- PCB exposed Copper areas plated with Immersion Gold

### MECHANICAL SPECIFICATIONS :

- Board Height 6U ( 9.187" ) ( 233.35mm )
- Board Length 11.75" ( 298mm )
- PCB Thickness 0.062" ( 1.6mm )
- Card Extender brackets (arms) on top & bottom (P/N : [5210211](#))

**Custom Extender design services available**  
please contact [inquire@vectorelect.com](mailto:inquire@vectorelect.com)

email us your requirements : [inquire@vectorelect.com](mailto:inquire@vectorelect.com)

11115 Vanowen St., North Hollywood, CA 91605, USA

Tel.: (818) 985 8208, (800) 423 5659; Fax : (818) 985 7708

**Circbord®, Vectorbord® and VectorPak® are registered trademarks of Vector Electronics & Technology, Inc.**  
**CompactPCI® is a registered trademark of PICMG. © 2001 Vector Electronics & Technology, Inc. - All Rights Reserved**